

1.2° 130mm 三相混合式步进电机 1.2° 130mm(NEMA52) 3phase hybrid stepper motor

基本性能/General Specification:

项目(Item)	性能(Specifications)
步距角(Step Angle)	1.2°
温 升(Temperature Rise)	80℃max
环境温度 (Ambient Temperature)	-20℃~+50℃
绝缘电阻(Insulation Resistance)	100 MΩ Min. ,500VDC
电气强度(Dielectric Strength)	1000VAC for 1minute
绝缘等级 (Insulation class)	B

电机规格/Electrical Specification:

型号 Model No.	运行电压 Operating Voltage	额定电流 Rated Current	电阻 Resistance	电感 Inductance	保持转矩 Holding Torque	空载频率 Noload Frequency	启动频率 Starting Frequency	重量 Weight	长度 Length
	VDC	A	Ω	mH	N.m	No.	g.cm	kg	mm
OE130H3P173	80~325	5	0.68	9.2	25	20000	2600	13.3	173
OE130H3P229	80~325	5	0.94	14.8	30	20000	2500	17.8	229
OE130H3P257	80~325	3	1.71	23.6	40	18000	2500	20	257
OE130H3P285	80~325	6	1.18	19.4	50	18000	2500	22.5	285

以上仅为代表产品，特殊产品可根据客户要求订制。

Above only for representative products, products of special request can be made according to the customer request.

电机外型图/Dimensions:(单位/Unit=mm)



接线图/Wiring Diagram:

