

1.8° 130mm 二相混合式步进电机 1.8° 130mm(NEMA52) 2phase hybrid stepper motor
基本性能/General Specification:


项目(Item)	性能(Specifications)
步距角(Step Angle)	1.8°
温 升(Temperature Rise)	80℃max
环境温度 (Ambient Temperature)	-20℃~+50℃
绝缘电阻(Insulation Resistance)	100 MΩ Min. ,500VDC
电气强度(Dielectric Strength)	1000VAC for 1minute
绝缘等级 (Insulation class)	B

电机规格/Electrical Specification:

型号 Model No.	运行电压 Operating Voltage	额定电流 Rated Current	电阻 Resistance	电感 Inductance	保持转 矩 Holding Torque	空载频 率 Noload Freque ncy	启动频 率 Starting Frequen cy	重量 Weig ht	长度 Length
	VDC	A	Ω	mH	N.m	No.	g.cm	kg	mm
OE130HS173-6004	80~325	6	0.75	12.6	25	25000	2300	13.3	173
OE130HS229-6004	80~325	6	0.83	13.2	30	25000	2300	18	229
OE130HS257-7004	80~325	7	0.73	11.7	40	23000	2200	19	257
OE130HS285-7004	80~325	7	0.66	10	50	23000	2200	22.5	285

以上仅为代表产品，特殊产品可根据客户要求订制。
Above only for representative products, products of special request can be made according to the customer request.

电机外型图/Dimensions:(单位/Unit=mm)



接线图/Wiring Diagram:

