

B42JBX-XC42BLDC

Specifications

Ratio Torque(Kg.cm) Speed(r/min) Model	1/6	1/8.5	1/16	1/24	1/36	Voltage (VDC)	Noload current (A)	Rated current (A)
	5	7	12	18	25			
B42JBX-XC42BLDC025J1000	166	115	60	40	28	24	≤0.3	≤0.6
B42JBX-XC42BLDC025J2000	330	230	120	80	55	24	≤0.4	≤1.1
B42JBX-XC42BLDC025J3000	500	350	185	120	83	24	≤0.5	≤1.6
B42JBX-XC42BLDC025J4000	666	470	250	160	110	24	≤0.6	≤2.1

Torque(Kg·cm) Speed(r/min) Ratio	1/6	1/8.5	1/16	1/24	1/36	Voltage (VDC)	Noload current (A)	Rated current (A)
	Model	5	7	12	18			
B42JBX-XC42BLDC025J1000	166	115	60	40	28	24	≤0.4	≤1.2
B42JBX-XC42BLDC025J2000	330	230	120	80	55	24	≤0.6	≤2
B42JBX-XC42BLDC025J3000	500	350	185	120	83	24	≤0.8	≤3
B42JBX-XC42BLDC025J4000	666	470	250	160	110	24	≤1.0	≤4

Reduction Ratio			Stage	L(mm)(XC42BLDC25)	L(mm)(XC42BLDC035)
1/4	1/6	1/8.5	1		
1/16	1/24	1/36	2		
1/64	1/96	1/144	3		

Can be customized.

Mechanical Dimensions

